

ATX™ JBD Series Pre-Drilled Terminal Junction Boxes

Flameproof

ATEX/IECEX:
Zone 1 and 2 – 21 and 22
Ex II 2 GD
IP66 – IK10

Applications

- Terminal junction boxes to facilitate electrical connections in hazardous areas.
- Ideal for use in wet or corrosive atmospheres.
- Designed for use in Zone 1 or 2 areas, where flammable gases or vapors are present either continuously or intermittently, such as:
 - Petroleum plants
 - Chemical plants
 - Refineries
 - Other industrial process facilities
- Designed for use in Zone 21 or 22 areas where flammable dusts are present either continuously or intermittently, such as:
 - Food processing
 - Dairy
 - Brewing
 - Silos

Features

- Flanged flameproof joint for square enclosures.
- Screwed flameproof joint for round enclosure.
- External earth crossing terminal.
- Supplied with one symmetrical zinc plated rail.
- Terminal block not supplied.
- Yellow laminated plastic nameplate with black lettering.
- Pre-Drilled entries.
- Operating temperature -40 °C to +55 °C (-40 °F to +131 °F).

Standard Materials

- Enclosure housing: gray painted cast iron and marine grade aluminum alloy
- Hardware: stainless steel

ATEX/IECEX Certifications and Compliances

- Certification Type CF2/A/B/C
 - Gas, Zones 1 and 2:
 - Conforming to ATEX 94/9/CE: Ex II 2 G
 - Type of Protection: Ex d IIB
 - Temperature Class: T6 for Ta ≤ +40 °C (+104 °F), T5 for Ta ≤ +55 °C (≤ +131 °F)
 - Dust, Zones 21 and 22:
 - Conforming to ATEX 94/9/CE: Ex II 2 D
 - Type of Protection: Ex td A21
 - Surface Temperature: T95 °C (T203 °F)
 - CE Declaration of Conformity: 50254
 - ATEX Certificate: LCIE 03 ATEX 6061X
- Certification Type CF1F
 - Gas, Zones 1 and 2:
 - Conforming to ATEX 94/9/CE: Ex II 2 G
 - Type of Protection: Ex d IIC
 - Temperature Class: T6 for Ta ≤ +40 °C (+104 °F), T5 for Ta ≤ +55 °C (≤ +131 °F)
 - Dust, Zones 21 and 22:
 - Conforming to ATEX 94/9/CE: Ex II 2 D
 - Type of Protection: Ex td A21
 - Surface Temperature: T95 °C (T203 °F)
 - CE Declaration of Conformity: 50257
 - ATEX Certificate: LCIE 03 ATEX 6044X
 - Index of Protection according EN/IEC 60529: IP66
 - Impact Resistance (shock): IK10
 - Internal Volume: > 2dm³ (122 in³) — 2 liters

JBDAB – Aluminum Version



JBDFC – Cast Iron Version



JBDFB – Cast Iron Version



- Certification Type CF20B
 - Gas, Zones 1 and 2:
 - Conforming to ATEX 94/9/CE: Ex II 2 G
 - ATEX/IEC Protection: Ex d IIB
 - Temperature Class: T6
 - Dust, Zones 21 and 22:
 - Conforming to ATEX 94/9/CE: Ex II 2 D
 - Type of Protection: Ex td A21
 - Surface Temperature: T80 °C (T176 °F)
 - Ambient Temperature: -40 °C to +55 °C (-40 °C to +131 °F)
 - CE Declaration of Conformity: 50229
 - ATEX Certificate: LCIE 02 ATEX 6057X
 - IECEx Certificate: IECEx LCI 08.0023X
 - Index of Protection according EN/IEC 60529: IP66
 - Impact Resistance (shock): IK10
 - Internal Volume: > 2dm³ (122 in³) — 2 liters

EURASEC Certification

- Certification Type CF2/A/B/C
 - EURASEC N° TC RU C-FR.Γ505.B.00911
- Certification Type CF1F
 - EURASEC N° TC RU C-FR.Γ505.B.00911


Options

- For use with equipment other than terminal blocks, please consult your local sales representative.

ATX™ JBD Series Pre-Drilled Terminal Junction Boxes

Flameproof

ATEX/IECEX:
Zone 1 and 2 – 21 and 22
II 2 GD
IP66 – IK10

Type	Dimensions mm (in)	Threaded Entry Per Side				Rail Length Capacity mm (in)	Weight kg(lb)	Volume dm ³ (in ³)	Catalog Number	Pack
		A	B	C	D					
Ex d IIB Enclosure in Cast Iron 										
CF2C	130 x 130 x 90 (5.12 x 5.12 x 3.54)	1 x M20	1 x M20	2 x M20	1 x M20	64 (2.52)	4 (8.82)	3 (183)	JBDFB131309D1	1
CF2A	205 x 145 x 127 (8.07 x 5.71 x 5.00)	2 x M20	1 x M20	3 x M20	1 x M20	120 (4.72)	9.4 (20.72)	3 (183)	JBDFB201413D2	1
CF2B	270 x 190 x 120 (10.63 x 7.48 x 4.72)	—	2 x M20 1 x M25	3 x M20	2 x M20	162 (6.38)	12.6 (27.78)	7 (427)	JBDFB271912D3	1
Ex d IIB Enclosure in Aluminum										
CF20B	370 x 270 x 208 (14.57 x 10.63 x 8.19)	—	3 x M20	5 x M20 1 x M32	3 x M20	260 (10.24)	12.8 (28.22)	24 (1465)	JBDAB372720D4	1
Ex d IIC Enclosure in Cast Iron										
CF1F	167 x 167 x 126 (6.57 x 6.57 x 4.96)	1 x M32	1 x M32	1 x M32	1 x M32	100 (3.94)	6.7 (14.77)	13 (793)	JBDFC161612D5	1
CF1F	167 x 167 x 126 (6.57 x 6.57 x 4.96)	1 x 1" NPT	1 x 1" NPT	1 x 1" NPT	1 x 1" NPT	100 (3.94)	6.7 (14.77)	13 (793)	JBDFC161612D6	1

Cast Iron Version Dimensions in Millimeters (Inches)

CF2C			CF1F			CF2A/CF2B				
Type	External		Internal			Fixings				
	A	B	C	D	E	F	G	H	K	Ø
CF2C	130 (5.12)	130 (5.12)	90 (3.54)	90 (3.54)	90 (3.54)	65 (2.56)	86 (3.39)	86 (3.39)	10 (0.39)	7 (0.28)
CF2A	202 (7.95)	144 (5.67)	127 (5.00)	155 (6.10)	95 (3.74)	65 (2.56)	156 (6.14)	98 (3.86)	12 (0.47)	7 (0.28)
CF2B	267 (10.51)	187 (7.36)	120 (4.72)	200 (7.87)	120 (4.72)	78 (3.07)	202 (7.95)	122 (4.80)	12 (0.47)	7 (0.28)

Aluminum Version Dimensions in Millimeters (Inches)

Type	External		Internal			Fixings				
	A	B	C	D	E	F	G	H	K	Ø
CF20B	370 (14.57)	270 (10.63)	208 (8.19)	300 (11.81)	175 (6.89)	159 (6.26)	250 (9.84)	245 (9.65)	15 (0.59)	11 (0.43)