

# THE MOSAIC FACTORY


## Certificate of Conformity

**Product:** Glazed mosaic TMF® Osiris Hertman collection, 51x59mm hexagon  
**Country of Origin:** CN  
**Type designation:** AFH-OH-13xxx  
**Patent depot nr.:** 015128547

**Technical Data:** Dry-pressed ceramic tiles for floorings and wall finishes, interior and exterior, with low water absorption  $E_b < 0.5\%$ , Group B I a, flat, glazed 51x59mm

Name of product	Glazed Mosaic	Nominal size (N)	51x59mm
Nature of the surface	Glazed (GL)	Work size	51x59x5,5mm
Group	B I a	Intended use	Wall finishes Interior and exterior

**Image:**



The above product has been tested for CE marking according to:

**EN 14411:2016** *Ceramic tiles – Definition, classification, characteristics, assessment and verification of constancy of performance and marking*

Clause	Properties	Test Method	Requirements	Results	Verdicts	
<b>A</b>	<b>Dimensions and surface quality</b>					
	Length	EN ISO 10545-2	±0,9mm	-0 mm - 0,1	Pass	
	Width	EN ISO 10545-2	±0,5mm	-0,1mm - 0,3	Pass	
	Thickness	EN ISO 10545-2	±0,5mm	0,0~+0,1mm	Pass	
<b>B</b>	<b>Physical properties</b>					
	Water absorption	EN ISO 10545-3	<0,5%	<0,22%	Pass	
	Breaking strength in N	EN ISO 10545-4	>1300	1901	Pass	
	Modulus of rupture, in Mpa	EN ISO 10545-4	Minimum 35	50,5	Pass	
	Resistance to abrasion	EN ISO 10545-7		750 - 2100	PEI 3-4	
	Thermal shock resistance	EN ISO 10545-9	Pass	Fully resistance	Pass	
	Crazing resistance Glazed tiles	EN ISO 10545-11	Pass	Fully resistance	Pass	
	Frost resistance	EN ISO 10545-12	Pass	Fully resistance	Pass	
	Slipperiness	DIN 51130				
		DIN 51097				
BS 7976		PTV Slider 96 dry		~63		
		PTV Slider 96 wet		~22		
	PTV Slider 55 dry					
	PTV Slider 55 wet					
<b>C</b>	<b>Chemical properties</b>					
	Resistance to staining	EN ISO 10545-14	Minimum Class 3	Class 5	Pass	
	Resistance to chemicals	EN ISO 10545-13	Minimum Class B	Class A	Pass	